

	1250AJP	1500AJP
Platform		
0.91 m x 1.83 m low mount platform	○	○
0.91 m x 2.44 m low mount platform	●	●
Side entry with drop bar mid rail	●	●
Side entry with inward swing gate	○	○
Multiple function operation	●	●
Full proportional drive joystick control with integral thumb steer switch	●	●
Full proportional main boom and swing joystick control	●	●
Variable speed dial control for telescope, platform rotate and tower	●	●
2.44 m articulating jib	●	●
JibPLUS® with 4 way axis jib including 125 degree horizontal motion	●	●
Powered side stow on jib	●	●
180 degree powered platform rotator	●	●
Platform console machine status light panel <sup>1</sup>	●	●
Load sensing system	●	●
AC power cable to platform	●	●
13 mm air line to platform	○	○
Engine & Transmission		
Deutz TCD 2.9 L4 (55.4 kW) diesel engine	●	●
Engine distress warning system <sup>2</sup>	○	○
Gull-wing turntable hoods	●	●
Swing-out engine tray	●	●
Spark arresting type muffler	●	●
Control ADE® - (Advanced Design Electronics System)	●	●
Adjustable swing drive	●	●
Hydrostatic transmission	●	●
Four wheel drive	●	●
Four wheel steer/Two Wheel Steer/Crab Steer	●	●
Horn	●	●
Functional Equipment & Accessories		
Selectable dual platform capacity system (230 kg/450 kg)	●	●
QuikStik® boom design feature	●	●
Drive-out extending axles	●	●
5 degree tilt alarm and indicator light	●	●
445/50D710 foam filled lug tread tyres	●	●
Oscillating front axle	●	●
Lifting/tie down lugs	●	●
On-board 4,000 W generator	○	○
SkyPower® package 7,500 W on-board generator	○	○
SkyWelder® package 250 amp welder in the platform <sup>3</sup>	○	○
SkyGlazier® package glass and panel tray	○	○
Nite-Bright® package <sup>4</sup>	○	○
Hour Meter	●	●
Ground control selector switch with key lock	●	●
Load Sensing Hydraulics	●	●
All motion alarm	○	○
Light package <sup>5</sup>	○	○
Platform worklights	○	○
Head and tail lights	○	○
Flashing amber beacon	○	○
Plugs and sockets	○	○
Hostile environment package <sup>6</sup>	○	○
Hydraulic oil cooler	○	○
Catalytic Purifier Muffler	●	—
Skyguard with beacon	○	○
Skyguard without beacon	○	●
Soft Touch 0.91 m x 1.83 m Platform Proximity System	○	○
Soft Touch 0.91 m x 2.44 m Platform Proximity System	○	○
Platform tool tray	●	●
Corner Storage tray	○	○
12V-DC auxiliary power	●	●
Standard ●   Option ○   Not Available —		

<sup>1</sup> Provides indicator lights at platform control console for system distress, low fuel, 5 degree tilt light, and foot switch status.

<sup>2</sup> Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.

<sup>3</sup> Available when integrated with the SkyPower® package.

<sup>4</sup> Consists of six 40 W lights, four turntable mounted lights and two platform mounted lights.

<sup>5</sup> Includes platform mounted work lights and head & tail lights.

<sup>6</sup> Includes console cover, boom wipers and cylinder bellows.

	400S	460SJ
Platform		
0.91 m x 1.83 m low mount platform	●	●
0.91 m x 2.44 m low mount platform	○	○
Side entry with drop bar mid rail	●	●
Side entry with inward swing gate	○	○
Multiple function operation	●	●
Full proportional drive joystick control with integral thumb steer switch	●	●
Full proportional main boom and swing joystick control	●	●
Multiple speed control for telescope and platform rotate	●	●
Selectable creep speed on drive / lift and swing functions	●	●
1.83 m articulating jib	—	●
180 degree powered platform rotator	●	●
Platform console machine status light panel <sup>1</sup>	●	●
Load sensing system	●	●
AC cable to platform	●	●
13 mm air line to platform	○	○
Engine & Transmission		
Deutz D2.3 L3 (36.4 kW) diesel engine	●	●
Engine distress warning/shut down system <sup>2</sup>	●	●
Dura Tough turntable hoods	●	●
Swing-out engine tray	●	●
Spark arresting type muffler	○	○
Control ADE® - Advanced Design Electronics System	●	●
Hydrostatic drive transmission	●	●
Four wheel drive	●	●
Horn	●	●
Functional Equipment & Accessories		
5 degree tilt alarm and indicator light	●	●
12 x 16.5 foam filled lug tread tyres	●	●
12 x 16.5 foam filled non marking tyres	○	○
14 x 17.5 foam filled lug tread tyres	○	○
Oscillating front axle	○	○
Lifting/tie down lugs	●	●
On-board 4,000 W generator	○	○
SkyPower® package 7,500 W on-board generator	○	○
SkyWelder® package 250 amp welder in the platform <sup>3</sup>	○	○
Nite-Bright® package <sup>4</sup>	○	○
Hour meter	●	●
Ground control selector switch with key lock	●	●
Tow Package	○	○
All motion alarm	○	○
Light package <sup>5</sup>	○	○
Platform worklights	○	○
Head and tail lights	○	○
Flashing amber beacon	○	○
Plugs & Sockets	○	○
Hostile environment package <sup>6</sup>	○	○
Hydraulic oil cooler	○	○
Catalytic Purifier Muffler	○	○
Skyguard with beacon	○	○
Skyguard without beacon	○	○
Soft Touch 0.91 m x 1.83 m Platform Proximity System	○	○
Soft Touch 0.91 m x 2.44 m Platform Proximity System	○	○
Platform tool tray	●	●
Corner storage tray	○	○
12V-DC auxiliary power	●	●
Standard ●   Option ○   Not Available —		

<sup>1</sup> Provides indicator lights at platform control console for system distress, low fuel, tilt light, and foot switch status.

<sup>2</sup> Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.

<sup>3</sup> Available when integrated with the SkyPower® package.

<sup>4</sup> Consists of six 40 W lights, four turntable mounted lights and two platform mounted lights.

<sup>5</sup> Includes platform mounted work lights and head & tail lights.

<sup>6</sup> Includes console cover, boom wipers and cylinder bellows.

