

	450AJ	520AJ
Platform		
0.76 m x 1.22 m low mount platform	○	○
0.76 m x 1.52 m low mount platform	○	○
0.76 m x 1.83 m low mount platform	●	●
Side entry with drop bar mid rail	●	●
Side entry with inward swing gate	○	○
Multiple function operation	●	●
Full proportional drive joystick control with integral thumb steer switch	●	●
Full proportional main boom and swing joystick control	●	●
Multiple speed control for lower boom, telescope and platform rotate	●	●
Selectable creep speed on drive / lift and swing functions	●	●
1.24 m articulating jib	●	●
180 degree powered platform rotator	●	●
Platform console machine status light panel ¹	●	●
Load sensing system	●	●
AC power cable to platform	●	●
13 mm air line to platform	○	○
Engine & Transmission		
Deutz D2.3 L3 (36.4 kW) diesel engine	●	●
Engine distress warning /shut down system ²	●	●
Dura Tough turntable hoods	●	●
Swing-out engine tray	●	●
Spark arresting type muffler	●	●
Control ADE® (Advanced Design Electronics) System	●	●
Hydrostatic drive transmission	●	●
Four wheel drive	●	●
Horn	●	●
Functional Equipment & Accessories		
5 degree tilt alarm and indicator light	●	●
33/1550 x 16.5 superwide foam filled tyres	●	●
315/55 D20 foam filled tyres	○	○
315/55 D20 foam filled non marking tyres	○	○
Oscillating front axle	●	●
Lifting/tie down lugs	●	●
On-board 4,000 W generator	○	○
SkyPower® package 7,500 W on-board generator	○	○
Hour meter	●	●
Ground control selector switch with key lock	●	●
All motion alarm	○	○
Light package ³	○	○
Platform worklights	○	○
Head and tail lights	○	○
Flashing amber beacon	○	○
Plugs & Sockets	○	○
Hostile environment package ⁴	○	○
Hydraulic oil cooler	○	○
Catalytic purifier muffler	○	○
Skyguard with beacon	○	○
Skyguard without beacon	○	○
Platform tool tray	●	●
Corner storage tray	○	○
12V-DC auxiliary power	●	●



Standard ● Option ○ Not Available —

¹ Provides indicator lights at platform control console for system distress, low fuel, tilt light, and foot switch status.
² Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.
³ Includes platform mounted work lights and head & tail lights.
⁴ Includes console cover, boom wipers and cylinder bellows.

	600A	n600A	600AJ
Platform			
0.91 m x 1.83 m low mount platform	●	●	●
0.91 m x 2.44 m low mount platform	○	○	○
Side entry with drop bar mid rail	●	●	●
Side entry with inward swing gate	○	○	○
Multiple function operation	●	●	●
Full proportional drive joystick control with integral thumb steer switch	●	●	●
Full proportional main boom and swing joystick control	●	●	●
Multiple speed control for lower boom, telescope and platform rotate	●	●	●
Selectable creep speed on drive / lift and swing functions	●	●	●
1.83 m articulating jib	—	—	●
180 degree powered platform rotator	●	●	●
Platform console machine status light panel ¹	●	●	●
Load sensing system	●	●	●
AC power cable to platform	●	●	●
13 mm air line to platform	○	○	○
Engine & Transmission			
Deutz D2011L04 (36.4 kW) diesel engine	●	●	●
Engine distress warning /shut down system ²	●	●	●
Gull-wing turntable hoods	●	●	●
Swing-out engine tray	●	●	●
Spark arresting type muffler	○	○	○
Control ADE® (Advanced Design Electronics) System	●	●	●
Hydrostatic drive transmission	●	●	●
Four wheel drive	○	—	○
Four wheel steer/Two wheel steer/Crab steer ³	○	●	○
Horn	●	●	●
Functional Equipment & Accessories			
3 degree tilt alarm and indicator light	●	●	●
IN 355/55D 625 foam filled lug tread tyres	●	—	●
14 x 17.5 solid segmented Airboss tyres	—	●	—
Oscillating front axle	○	—	○
2.13 m narrow frame	—	●	—
Lifting/tie down lugs	●	●	●
On-board 4,000 W generator	○	○	○
SkyPower® package 7,500 W on-board generator	○	○	○
SkyWelder® package 250 amp welder in the platform ⁴	○	○	○
Nite-Bright® package ⁵	○	○	○
Hour meter	●	●	●
Ground control selector switch with key lock	●	●	●
Tow package	○	○	○
All motion alarm	○	○	○
Light package ⁶	○	○	○
Platform worklights	○	○	○
Head and tail lights	○	○	○
Flashing amber beacon	○	○	○
Plugs & Sockets	○	○	○
Hostile environment package ⁷	○	○	○
Hydraulic oil cooler	○	○	○
Catalytic purifier muffler	○	○	○
Skyguard with beacon	○	○	○
Skyguard without beacon	○	○	○
Platform tool tray	●	●	●
Soft Touch 0.91 m x 1.83 m Platform Proximity System	○	—	○
Soft Touch 0.91 m x 2.44 m Platform Proximity System	○	—	○
Corner storage tray	○	○	○
12V-DC auxiliary power	●	●	●

Standard ● Option ○ Not Available —

¹ Provides indicator lights at platform control console for system distress, low fuel, tilt light, and foot switch status.
² Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.
³ Only available with four wheel drive on models 600A and 600AJ with 2.49 m wide chassis and 800A and 800AJ.
 Only available with two wheel drive on models n600A and n600AJ with 2.13 m chassis.
⁴ Available when integrated with the SkyPower® package
⁵ Consists of six 40 W lights, four turntable mounted lights and two platform mounted lights.
⁶ Includes platform mounted work lights and head & tail lights.
⁷ Includes console cover, boom wipers and cylinder bellows.

