**Articulating Boom Lifts Articulating Boom Lifts** 

Platform	740A.
0.91 m x 1.83 m low mount fall arrest platform	•
Rear entry with hinged mid rail	
Multiple function operation	
Full proportional drive joystick control with integral thumb steer switch	
Full proportional main boom and swing joystick control	
Multiple speed control for lower boom, telescope and platform rotate	
Selectable creep speed on drive, lift and swing functions	
1.83 m articulting jib	
180 degree powered platform rotator	
Platform console machine status light panel <sup>1</sup>	
Load sensing system	<u>~</u>
AC power cable to platform	
13 mm Air line to platform	0
Engine & Transmission	
Deutz TD 2.9 L4 (50 kW) diesel engine	•
Engine distress warning / shut down system <sup>2</sup>	•
Gull-wing turntable hoods	•
Swing-out engine tray	•
Spark arresting type muffler	•
Control ADE® (Advanced Design Electronics) System	•
Hydrostatic drive transmission	•
Four wheel drive	•
Four wheel steer / Two wheel steer / Crab steer	•
Horn	•
Functional Equipment & Accessories	
144 km/h jet blast rating to ARP 1328 standard	•
3 degree tilt alarm and indicator light	•
18-625 foam filled lug tread tyres	•
Fixed front axle	•
Lifting / tie down lugs	•
On-board 4,000 W generator	•
Hourmeter	•
Ground control selector switch with key lock	•
All motion alarm	0
Platform worklights	0
Flashing amber beacon	0
Plugs and Sockets	0
Hostile Environment Kit <sup>3</sup>	0
Hydraulic oil cooler	0
Catalytic purifier muffler	•
Skyguard with beacon	0
Skyguard without beacon	0
Soft Touch 0.91 m x 1.83 m Platform Proximity System	0
Platform tool tray	•
Corner storage tray	0
12V-DC auxilliary power	•

Standard ● Option ○ Not Available —



Provides indicator lights at platform control console for system distress, low fuel, tilt light and foot switch status.
 Low oil pressure and high coolant temperature alarms with shut down enabled / disabled by analyser

Dia 4.6 a mar	800A	800A
Platform	_	
0.91 m x 1.83 m low mount platform	<u> </u>	
0.91 m x 2.44 m low mount platform	0	0
Side entry with drop bar mid rail Side entry with inward swing gate	0	<u> </u>
Multiple function operation		
Full proportional drive joystick control with integral thumb steer switch		<del>`</del>
Full proportional main boom and swing joystick control		
Multiple speed control for telescope, lower boom and platform rotate	•	•
Selectable creep speed on drive / lift and swing functions	•	•
1.83 m articulating jib		•
180 degree powered platform rotator	•	•
Platform console machine status light panel <sup>1</sup>	•	•
Load sensing system	•	•
AC power cable to platform	•	•
I3 mm air line to platform	0	0
Engine & Transmission		
Deutz TD 2.9 L4 (50 kW) diesel engine	•	•
Engine distress warning /shut down system <sup>2</sup>	•	•
Gull-wing turntable hoods	•	•
Swing-out engine tray	0	0
Spark arresting type muffler	•	•
Control ADE® (Advanced Design Electronics) System	•	•
Hydrostatic drive transmission	•	•
our wheel drive	0	0
Four wheel steer/Two wheel steer/Crab steer <sup>3</sup>	0	0
Horn	•	•
QuikStik® boom design  8 degree tilt alarm and indicator light	•	•
18 - 625 foam filled lug tread tyres	<u> </u>	
Oscillating front axle	0	0
Load sensing boom function pump	•	•
Lifting/tie down lugs		• •
On-board 4,000 W generator SkyPower® package 7,500 W on-board generator	O 	0
SkyWelder® package 250 amp welder in the platform 4	0	0
Hour meter	•	•
Ground control selector switch with key lock		-
Tow package	0	
All motion alarm	0	0
Light package 5	0	0
Platform worklights	0	0
Head and tail lights	0	0
Flashing amber beacon	0	0
Plugs & Sockets	0	0
Hostile environment package <sup>6</sup>	0	0
Hydraulic oil cooler	0	0
Catalytic purifier muffler	•	•
Skyguard with beacon	0	0
Skyguard without beacon	0	0
Soft Touch 0.91 m x 1.83 m Platform Proximity System	0	0
Soft Touch 0.91 m x 2.44 m Platform Proximity System	0	0
Platform tool tray	•	•
Corner storage tray	0	0

Standard ● Option ○ Not Available —

1 Provides indicator lights at platform control console for system distress, low fuel, tilt light, and foot switch status.

41

<sup>2</sup> Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.

<sup>3</sup> Only available with four wheel drive on models 800A and 800AJ.

Available when integrated with the SkyPower® package
 Includes platform mounted work lights and head & tail lights.
 Includes console cover, boom wipers and cylinder bellows.

©2018, JLG Industries, Inc. ©2018, JLG Industries, Inc.

<sup>&</sup>lt;sup>3</sup> Includes console cover, boom wipers and cylinder bellows