

	X14J	X17J	X19J	X23J
Platform				
0.69 m x 1.30 m Aluminium 2 person platform	●	—	●	●
0.62 m x 1.30 m Aluminium 2 person platform	—	—	—	—
0.76 m x 1.30 m Aluminium 2 person platform	—	●	—	—
0.59 m x 0.79 m Aluminium 1 person platform	○	—	○	○
0.69 m x 0.79 m Aluminium 1 person platform	—	—	—	—
0.73 m x 0.79 m Aluminium 1 person platform	—	○	—	—
Slide bar rear entry	●	●	●	●
Footswitch	●	●	●	●
Full proportional control	●	●	●	●
Articulating jib	●	●	●	●
Powered platform rotator (124°)	—	●	●	●
Remote Control (via cable to platform)	●	—	●	●
Full Remote Control of drive and stabilization	—	●	—	—
Multi-lingual LCD display on platform console	●	●	●	●
Platform console position sensor and lock	●	●	●	●
Envelope management load sensing system	●	●	●	●
Platform designed for ease of removal/changeover	●	●	●	●
AC Cable to platform	●	●	●	●
6.5 mm (1/4") air/water line to platform	●	●	●	●
Engine & Transmission				
Honda GX270 - 6.6 kW (9HP) Gasoline Engine	●	—	—	—
Honda GX390 - 9.6 kW (13HP) Gasoline Engine	○	—	—	—
Honda iGX440 - 11 kW (15HP) Gasoline Engine	—	●	●	●
Hatz IB30 - 5.4 kW (7.5HP) Diesel Engine	○	—	—	—
Hatz IB40 - 7.5 kW (10HP) Diesel Engine	—	○	○	—
Perkins 402.05 - 10.2 kW (14HP) Diesel Engine	—	—	—	○
220V, 50Hz - 2.2 kW Electric Engine	●	●	●	●
110V, 50Hz - 2.2 kW Electric Engine	○	○	○	○
Engine protection	●	●	●	●
100A/hr, 48V Lithium ion power pack ¹	○	○	○	—
100A/hr 72V Lithium ion power pack ¹	—	—	—	○
1.24 m x 0.18 m x 0.30 m Low Profile Black Rubber Tracks	●	●	●	—
1.24 m x 0.18 m x 0.30 m Low Profile Non Mark Rubber Tracks	○	○	○	—
1.24 m x 0.18 m x 0.31 m High Profile Black Rubber Tracks	○	○	○	—
1.76 m x 0.23 m x 0.38 m High Profile Black Rubber Tracks	—	—	—	●
1.76 m x 0.23 m x 0.38 m High Profile Non Mark Rubber Tracks	—	—	—	○
Functional Equipment & Accessories				
Automatic Stabilization	●	●	●	●
Automatic Stabilization with Variable Outrigger Footprint	—	—	—	●
Non Mark Outrigger Pads	●	●	●	●
Cylinder Rod Protection on Outriggers	●	●	●	●
Automatic cut-out when out of level	●	●	●	●
Powered track extensions/'retraction	—	●	●	●
361° non-continuous turntable rotation	●	●	●	●
300° non-continuous turntable rotation	—	—	—	—
Turntable alignment sensor and gauge	●	●	●	●
Three emergency descent systems	●	●	●	●
Electro-hydraulic controls	●	— ²	●	●
Full pressure hydraulic controls	—	● ²	—	—
2nd (high) Drive speed	○	○	○	●
Lifting/Tie down points	●	●	●	●

Standard ● Option ○ Not Available —



¹ Replaces both combustion and electric engines
² Combination of radio control and hydraulic control on this model

	X15J Plus	X17J Plus	X20J Plus	X26J Plus
Platform				
0.69 m x 1.30 m Aluminium 2 person platform	●	●	●	●
Slide bar rear entry	●	●	●	●
Footswitch	●	●	●	●
Full proportional control	●	●	●	●
Articulating jib	●	●	●	●
Powered platform rotator (124°)	●	●	●	●
Remote Control (via cable to platform)	●	●	●	●
Full Remote Control of drive and stabilization	●	●	●	●
Multi-lingual LCD display on platform console	●	●	●	●
Platform console position sensor and lock	●	●	●	●
Envelope management load sensing system	●	●	●	●
Platform designed for ease of removal/changeover	●	●	●	●
AC Cable to platform	●	●	●	●
6.5 mm air line to platform	●	●	●	●
Engine & Transmission				
Honda iGX440 - 11 kW (15HP) Gasoline Engine	●	●	●	—
Hatz IB40 - 7.5 kW (10HP) Diesel Engine	○	○	—	—
Perkins 402.05 - 10.2 kW (14HP) Diesel Engine	—	—	○	—
Kubota D905 - 16 kW (21.6HP) Diesel Engine	—	—	—	●
220V, 50Hz - 2.2 kW Electric Engine	●	●	●	●
110V, 50Hz - 2.2 kW Electric Engine	○	○	○	○
Engine protection	●	●	●	●
100A/hr, 48V Lithium ion power pack ¹	○	○	—	—
100A/hr 72V Lithium ion power pack ¹	—	—	○	—
100A/hr 83V Lithium ion power pack ¹	—	—	—	○
1.24 m x 0.18 m x 0.30 m Low Profile Black Rubber Tracks	●	●	—	—
1.24 m x 0.18 m x 0.30 m Low Profile Non Mark Rubber Tracks	○	○	—	—
1.46 m x 0.2 m x 0.35 m Low Profile Black Rubber Tracks	—	—	●	—
1.46 m x 0.2 m x 0.35 m Low Profile Non Mark Rubber Tracks	—	—	○	—
1.76 m x 0.23 m x 0.38 m High Profile Rubber Tracks	—	—	—	●
1.76 m x 0.23 m x 0.38 m High Profile Non Mark Rubber Tracks	—	—	—	○
Functional Equipment & Accessories				
Non Mark Outrigger Pads	●	●	●	●
Cylinder Rod Protection on Outriggers	●	●	●	●
Automatic cut-out when out of level	●	●	●	●
Powered track extensions/'retraction	●	●	●	●
360° non-continuous turntable rotation	●	●	●	●
Turntable alignment sensor and gauge	●	●	●	●
Three emergency descent systems	●	●	●	●
Electro-hydraulic controls	●	●	●	●
Full pressure hydraulic controls	—	—	—	—
2nd (high) Drive speed	●	●	●	●
Lifting/Tie down points	●	●	●	●
Side Fork Pockets	—	●	●	●

Standard ● Option ○ Not Available —