

Platform

2.50 m X 5.35 m Platform (7.55 m extended)
Single hydraulic powered deck extension
Composite treated wooden floor
Fold-down/drop-down handrails
Self-closing gate
Removable platform console box
Platform console function status LED's¹
Lanyard attach points
Proportional drive control
Load sensing system
Two speed drive selection
Hydraulic differential lock

Power & Transmission

Deutz D2011L04i (42kW) diesel engine
Gull wing steel engine / valve compartment hoods
Engine monitoring system with integral shut-down
Hydraulic transmission
Four wheel drive
Drive disconnect/brake release

¹ Indicator LED lights on platform control console for tilt, high drive, lift, drive and overload interlocks.

Functional Equipment & Accessories

Nivolux self-levelling hydraulic jacks
Steel mesh scissor arm guards
315/80 R22.5 foam filled lug tread tyres
Oscillating rear axle
3 degree tilt indicator light with cut-out
Ground control selector switch with key lock
Full grease lubrication on all scissor arm bushings
Scissor maintenance prop
Manual descent system
Hour meter
Horn
Travel alarm
Lifting/tie down lugs

Available Options

AC cable to platform



JLG Industries Inc.
Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands
Tel: +31 (0)23 565 5665
Fax: +31 (0)23 557 2493
e-mail address: europe@jlg.com
www.jlgeurope.com
An Oshkosh Corporation Company

Printed in UK
FORM No.: DS021
PART NO.: DS021-ENGLISH



245-25

| | |
|-----------------------------------|-----------------------------|
| A. Platform height - elevated | 24.50 m |
| B. Platform height - lowered | 3.14 m |
| C. Platform railing height | 1.10 m |
| D. Stowed height (rails folded) | 3.24 m |
| E. Platform size | 2.50 m x 5.35 m |
| F. Platform length fully extended | 7.80 m |
| G. Overall width | 2.50 m |
| H. Overall length | 5.78 m |
| I. Wheelbase | 3.90 m |
| Ground clearance | 0.26 m |
| Platform capacity | 750 kg |
| Capacity on deck extension | 750 kg |
| Lift/lower time | 125 / 80 sec |
| Maximum drive height | 21.00 m |
| Deck extension | Hydraulic |
| Machine weight ¹ | 16,300 kg |
| Maximum ground bearing pressure | 6.0 kg/cm ² |
| Drive speed - high | 2.3 km/h |
| Drive speed - elevated | 0.5 km/h |
| Gradeability (4WD) | 25% |
| Turning radius - inside | 1.50 m |
| Turning radius - outside | 6.20 m |
| Axle oscillation | 0.15 m (±) |
| Tyres | 315/80 R22.5 Foam Filled |
| Diesel engine | 42 kW Deutz D2011L04i |
| Fuel tank capacity | 90 L |
| Hydraulic system | 325 L |

¹ Certain options or country standards may increase weight and/or dimensions.

