

	1850SJ
Platform	
0.91 m x 2.44 m low mount platform	●
Side entry with drop bar mid rail	●
Side entry with inward swing gate	○
Multiple function operation	●
Full proportional drive joystick control with integral thumb steer switch	●
Full proportional main boom and swing joystick control	●
Variable speed dial control for telescope and platform rotate	●
3.96 m to 6.10 m Telescoping jib	●
Powered side stow on jib	●
180 degree powered platform rotator	●
Platform console machine status light panel ¹	●
Load sensing system	●
AC cable to platform	●
13 mm air line to platform	○
Engine & Transmission	
Deutz TCD 3.6 L4 (74.4 kW) diesel engine	●
Engine distress warning/shut down system ²	○
Gull-wing hoods	●
Swing-out engine tray	●
Spark arresting type muffler	●
Control ADE® (Advanced Design Electronics) System	●
Adjustable swing drive	●
Hydrostatic transmission	●
Four wheel drive	●
Four wheel steer/two wheel steer/crab steer	●
Horn	●
Functional Equipment & Accessories	
Selectable dual platform capacity system (230 kg/450 kg)	●
Drive-out extending axles	●
4 degree tilt alarm and indicator light	●
445/50D710 foam filled lug tread tyres	●
Lifting/tie down lugs	●
SkyPower® package 7,500 W on-board generator	○
SkyWelder® package 250 amp welder in the platform ³	○
SkyGlazier® package glass and panel tray	○
Nite-Bright® package ⁴	○
Hour meter	●
Ground control selector switch with key lock	●
Load sensing hydraulics	●
All motion alarm	○
Light package ⁵	○
Platform worklights	○
Head and tail lights	○
Flashing amber beacon	○
Plugs & Sockets	○
Hostile environment package ⁶	○
Hydraulic oil cooler	○
Catalytic purifier muffler	●
Soft Touch 0.91 m x 1.83 m Platform Proximity System	○
Soft Touch 0.91 m x 2.44 m Platform Proximity System	○
Skyguard with beacon	○
Skyguard without beacon	○
Platform tool tray	●
Corner storage tray	○
12V-DC auxiliary power	●
Standard ● Option ○ Not Available —	

¹ Provides indicator lights at platform control console for system distress, low fuel, tilt light, and foot switch status.
² Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.
³ Available when integrated with the SkyPower® package.
⁴ Consists of six 40 W lights, four turntable mounted lights and two platform mounted lights.
⁵ Includes platform mounted work lights and head & tail lights.
⁶ Includes console cover, boom wipers and cylinder bellows.

	260MRT
Platform	
1.65 m x 2.59 m steel platform (deck extension retracted)	●
1.22 m manual front deck extension	●
Fold down handrails	●
Self-closing gate	●
Lanyard attach points	●
Proportional drive control with thumb steer	●
Proportional lift/lower speed control	●
Joystick enable for lift and drive	●
Moveable and removable platform console box	●
Load sensing system	●
Engine & Transmission	
Kubota D1005 (17.5 kW) diesel engine	●
Programmable "Personality" settings	●
On-board self-diagnostic testing	●
Engine distress warning/shut down system ¹	●
Hydrostatic drive with anti stall function	●
Two speed drive selection	●
Four wheel drive	●
Functional Equipment & Accessories	
3 degree tilt alarm and indicator light	●
Steel scissor guards	●
26 x 12 foam filled loader lug tread tyres	●
Hydraulic levelling jacks	○
Lifting/tie down lugs	●
Hour meter	●
Ground control selector switch with key lock	●
Lubrication free scissor arm bushings	●
Scissor maintenance prop	●
Horn	●
Descent alarm	○
All motion alarm	○
AC power cable to platform	●
13 mm air line to platform	○
Platform work lights ²	○
Flashing amber beacon	○
Plugs & Sockets	○
Cylinder bellows	○

Standard ● Option ○ Not Available —



¹ Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.
² Includes four 40 W platform mounted halogen floodlights