

	330LRT	430LRT	530LRT
Platform			
1.91 m x 4.06 m steel platform (deck extensions retracted)	●	●	●
1.22 m manual front deck extension	○	○	●
1.22 m manual rear deck extension	●	●	○
1.91 m x 4.06 m Megadeck steel platform (deck extensions retracted)	—	—	○
Fold down handrails	○	—	●
Dual side entry with half swing gates	●	●	●
Lanyard attach points	●	●	●
Proportional drive control with thumb steer	●	●	●
Proportional lift/lower speed control	●	●	●
Joystick enable for lift and drive	●	●	●
Moveable and removable platform console box	●	●	●
Load sensing system	●	●	●
Engine & Transmission			
Kubota D1305 (21.7 kW) diesel engine	●	●	●
Programmable “Personality” settings	—	—	●
On-board self-diagnostic testing	●	●	●
Engine distress warning/shut down system ¹	●	●	●
Hydrostatic drive with anti stall function	●	●	●
Two speed drive selection	●	●	●
Four wheel drive	●	●	●
Functional Equipment & Accessories			
3 degree tilt alarm and indicator light	●	●	●
Guardless system with audio visual alarm	—	—	●
Steel scissor guards	●	●	—
33/1550 x 16.5 foam filled loader lug tread tyres	○	○	—
IN315/55 D20 foam filled loader lug tread tyres	○	○	—
12 x 16.5 foam filled loader lug tread tyres	○	○	●
395/45 D20 foam filled low profile tyres	—	—	○
12 x 16.5 foam filled non mark tyres	○	○	○
395/45 D20 foam filled non mark tyres	—	—	○
Oscillating front axle	—	—	●
Oscillating front axle with DUS	●	●	—
Hydraulic levelling jacks	○	○	●
Lifting/tie down lugs	●	●	●
SkyPower® 7,500W on-board generator package	○	○	○
Hour meter	●	●	●
Ground control selector switch with key lock	●	●	●
Lubrication free scissor arm bushings	●	●	●
Scissor maintenance prop	●	●	●
Horn	●	●	●
Descent alarm	○	○	○
All motion alarm	○	○	○
AC power cable to platform	●	●	●
13 mm air line to platform	○	○	○
Platform work lights (LED)	○	○	○
Nite-Bright® package ²	—	—	○
Nite-Bright® package ³	○	○	—
Flashing amber beacon	○	○	○
Plugs & Sockets	○	○	○
Catalytic purifier muffler	○	○	—
Spark arresting type muffler	○	○	—
Pipe racks (Rail mounted)	○	○	○
12V-DC auxiliary power ⁴	○	○	—

Standard ● Option ○ Not Available —



¹ Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.

² Includes four platform mounted LED floodlights