

Model 15MSP

MOBILE STOCK PICKER



Performance

Platform Height	15 ft 3 in.	4.65 m
Working Height	21 ft 3 in.	6.48 m
Drive Height	Max. Platform Height	
Stowed Height	78 in.	198 cm
Platform Entry Height	18 in.	46 cm
Platform Size (W x L)	28 x 26 in.	71 x 66 cm
Overall Vehicle Length		
Chassis Length	53.5 in.	136 cm
Stock Picking Platform	74 in.	188 cm
Extension Platform Retracted	53 in.	135 cm
Overall Vehicle Width		
Chassis Length	29.5 in.	75 cm
Stock Picking Platform	31.5 in.	80 cm
Gross Vehicle Weight	2,425 lb	1,100 kg
Platform Capacity	500 lb	227 kg
Drive Speed		
Platform Lowered	3.5 mph	5.6 km/h
Platform Elevated	0.6 mph	1 km/h
Turning Radius	Zero	
Gradeability	30%	
Underclearance	2 in.	5 cm

Standard Specifications

Power Source

Batteries	Two Sealed 100 amp-hr Maintenance-Free Glass Mat (AGM)	
Battery Charger	25 Amp Automatic	
Drive System	4 Brush Direct Electric (planetary gear)	

Tires

Rear Drive & Steer Wheels	12.6 x 4 in.	32 x 10 cm
Non-Marking Front Caster Wheels	8 x 2.5 in.	20 x 6 cm

Standard Features

- Heavy Duty Planetary Gear Drive Motors with 5 Times the Life of Previous Models
- Heavy Duty Pistol-Grip Joystick
- Low Maintenance Anodized Aluminum Mast
- Stock Picking Platform with Front and Side Entry—Flexible or Fixed Rail Set Up for Platform Access
- Safety Interlocked Controls
- Variable Speed Elevation Controls
- Automatic Pothole Protection System
- 1-1/2 Degree Tilt Alarm and Control
- Automatic Five-Hour Battery Charger
- Key Lock Main Power Switch
- Automatic Power-Off Battery Saver Control
- Battery Discharge Indicators—Platform and Base
- Transportation Tie Downs
- Built-In Fork Truck Pockets
- Lanyard Attachment Anchor
- Hourmeter
- All Motion Alarm
- Flashing Amber Beacon
- Horn
- ANSI, OSHA & CSA Compliant

Accessories & Options

- Fold Down Material Tray Platform 25.25 x 27.75 in. (65 x 70 cm)
- Tool Tray 8 in. W x 18 in L x 5 in. D (20 x 46 x 13 cm)
- Programmable 4-Digit Security Lock
- 110 Volt Double Receptacle on Platform
- Lifting Eye for a Crane Hook
- Obstruction Sensing Device (Stock Picking Platform only)
- Fluorescent Light Tube Caddy
- 2nd Flashing Amber Beacon (Top of Mast)
- 8 ft Fluorescent Light Crate Carrier
- Rug Carrier
- Bike Carrier



The JLG "1 & 5" Warranty

JLG Industries, Inc. backs its products with its exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable OSHA Regulations in 29 CFR 1910.67, 29 CFR 1926.453, ANSI A92.5-2006, and CSA Standard CAN3-B354.2-M82, as originally manufactured for intended applications.

Form No.: SS-15MSP-0106
Part No.: 3132120
R101303
Printed in USA



JLG Industries, Inc.

1 JLG Drive
McConnellsburg, PA 17233-9533
Telephone 717-485-5161
Toll-free in US 877-JLG-LIFT
Fax 717-485-6417
www.jlg.com

The JLG Group is an Oshkosh Corporation Company