


JLG® Vertical Lifts

AMI AND AM SERIES



Main Features

- Low-maintenance anodized mast.
- 110 volt double receptacle in platform.
- Lanyard attachment anchor for body harness.
- Non-marking tires.
- Quick-change platform mounts.
- Quick-change 26 in. W x 28 in. L (66 x 71 cm) — gull-wing entry platform.
- Roller loading device: for loading on pickup trucks — AM models only.

19AMI


AM Series Push-Around Vertical Lifts

Platform Height	19 ft 1 in. (5.81 m)
Platform Capacity	350 lb (160 kg)
Overall Height Stowed	78 in. (1.98 m)
Overall Length	55 in. (1.42 m)
Overall Width	34 in. (86 cm)
Outrigger Footprint (LxW)	n/a
Turning Radius	n/a
Weight	1,130 lb (513 kg)

Available Options

26 x 26 Right Side Entry (Slide Bar)	•
Narrow Quick-Change Platform ¹	•
Extension Quick-Change Platform ²	•
Tool Tray ³	•
Fluorescent Light Tube Caddy ⁴	•

1. 22 in. W x 22 in. L
2. 26 in. W x 26 in. L — Retracted, 26 in. W x 49 in. L — Extended (AMI Only; 300 lb capacity).
3. 8 in. W x 18 in. L x 5 in. D — Hangs from top platform rail.
4. Hangs from top platform rail.



Main Features

- Low-maintenance anodized mast.
- 110 volt double receptacle in platform.
- Lanyard attachment anchor for body harness.
- Non-marking tires.
- Quick-change platform mounts.
- Quick-change 26 in. W x 28 in. L (66 x 71 cm) — gull wing entry platform.
- Roller loading device: for loading on pickup trucks — AM models only.

20AM

25AM

30AM

36AM

41AM

AM Series Push-Around Vertical Lifts

Platform Height	20 ft (6.1 m)	24 ft 10 in. (7.57 m)	29 ft 7 in. (9.01 m)	36 ft (10.97 m)	40 ft 5 in. (12.32 m)
Platform Capacity	350 lb (159 kg)	350 lb (159 kg)	350 lb (159 kg)	300 lb (136 kg)	300 lb (136 kg)
Overall Height Stowed	78 in. (1.98 m)	78 in. (1.98 m)	78 in. (1.98 m)	104.5 in. (2.65 m)	104.5 in. (2.65 m)
Overall Length	55 in. (1.40 m)	57 in. (1.46 m)	57 in. (1.46 m)	58 in. (1.47 m)	60.5 in. (1.54 m)
Overall Base Width	29.5 in. (75.00 cm)	29.5 in. (75.00 cm)	29.5 in. (75.00 cm)	29.5 in. (75.00 cm)	29.5 in. (75.00 cm)
Outrigger Footprint (LxW)	62 x 54.5 in. (1.57 x 1.38 m)	62 x 54.5 in. (1.57 x 1.38 m)	74.7 x 71.6 in. (1.89 x 1.81 m)	79 x 79 in. (2.01 x 2.01 m)	80.5 x 86 in. (2.04 x 2.18 m)
Weight (AC)	740 lb (336 kg)	825 lb (374 kg)	890 lb (404 kg)	1,060 lb (481 kg)	1,100 lb (499 kg)
Weight (DC)	860 lb (390 kg)	905 lb (411 kg)	940 lb (426 kg)	1,160 lb (526 kg)	1,230 lb (588 kg)

Available Options

26 x 26 Right Side Entry (Slide Bar)	•	•	•	•	•
Narrow Quick-Change Platform ¹	•	•	•	•	•
Straddle Kit ² — AM Models Only — Includes Ladder	•	•	•	•	•
43 in. (1.09 m) Clearance	•	•	•	•	•
55 in. (1.4 m) Clearance	•	•	•	•	•
Straddle Outrigger Interlock Adapter ² — Mounts on the AM Lift (AM only)	•	•	•	•	•
Tool Tray ³	•	•	•	•	•

1. 22 in. W x 22 in. L (not available on 41AM).
2. JLG recommends the 26 x 26 right side entry platform and straddle outrigger interlock adaptor with this option.
3. 8 in. W x 18 in. L x 5 in. D — Hangs from top platform rail.