

JLG° RS Telehandlers

SIMPLICITY WITHOUT COMPROMISE

JLG introduces the RS Series of Telehandlers.
All set to go to work, the RS Series is available in two models. Both models offer added comfort, improved serviceability and a lower cost of ownership. Constructed with proven components, the RS series telehandlers are an attractive and productive addition to your fleet.

ALL THE POWER AND LIFT YOU NEED







Proven Power Train Both RS Models come standard with integrated powershift 3-speed transmission and feature Dana axles.



Straightforward to Service Simplified boom design so there is less service and easier access provided.



Payload and **Working Height**

The JLG RS Series feature a 3.6t/4.0t max. lift capacity and a 14m/17m max. lift height respectively.



Minimising Cleaning Time

The JLG 3614RS and 4017RS telehandlers have cabins that can be cleaned using a pressure washer typically used to clean the exterior.



FIELDPROVEN RELIABILITY -

Reliability starts with a proven powertrain. The JLG 3614RS and 4017RS telehandlers feature Dana axles and transmissions paired with Deutz engines, all components that have

been proven over time and add to reliability in the field.



UNCOMPROMISED COMFORT

The cab was designed with the operator in mind allowing them to acclimate to new equipment more quickly. Single joystick controls reduce complexity. And features such as improved sightlines,

enhanced visibility, mechanical suspension seats, and thoughtfully positioned armrests all enhance operator comfort and productivity. Ultimately, these types of features make machines easier to rent.



Cabin Controls
Well spaced cabin with
controls placed in front
of the operator.



Driving Experience
Longer wheel base provides
greater stability and comfort
when driving as well as
landing loads.



Fuel-efficient Engine

JLG RS Series Telehandlers are
equipped with a dependable

Deutz TCD 3.6L4 Stage 4
engine, providing 55.4kW.



Powerfull Hydraulics
The gear pump provides
100 l/min flow at 270 bar
generating competitive
cycle times.





CHOOSE YOUR STEERING MODE



Front wheel steer when driving on the road.



All-wheel steer to help reduce the turning radius in confined areas.



Crab steer for sideways movement and precise positioning before lifting.

ALL ACCESS FOR ALL TERRAIN

JLG RS Series telehandlers are designed to take on almost any kind of job. A high ground clearance, with a low center of gravity and 4-wheel drive is a particular advantage traversing rough terrain. Standard frame leveling adds to your level of efficiency, especially when loading on slopes and uneven terrain.



FRAME LEVELLING

The front axle of the 3614RS and the 4017RS can oscillate on slopes up to 10 degrees.

TURN CORNERS

A tight turning radius helps you get around on crowded job sites.

SIMPLICITY IN UPKEEP

The JLG RS Series of telehandlers deliver convenience of maintenance and upkeep. With the external telescopic cylinder being located on the outside, rather than inside the boom, it provides quicker and easier access for service technicians.



Less service and fewer points for potential hydraulic leaks due to single compensation lift cylinder.










Light Material Bucket Clean up the job site, spread gravel or for loading and leveling.



Forks that are fully floating and adjustable side-to-side for efficient load entry and exit.



Truss Boom

Allows operator to set trusses and wall sections for wood and steel building construction. Available with or without winch.



2m Pallet Forks

Ideal for large, flat materials, limiting damage during transport such as drywall or steel plates. Fork positioning carriage 1225mm, incl. 50 x100x1200 forks



4-In-One bucket

Carry out multiple activities with the 4-in-one (cylinder operated) bucket.



Fork Mounted Lifting Hook

Add versatility to any standard carriage by lifting and lowering objects without changing attachments.



greater ease.

Enclosed Cab



Hitches



Rotating Beacon

Brick Guard



Inclinometer

Air

Conditioning



Sun Blind

Rear Road

Lights



Non Slip Floor Mat



Front Road Lights



Radio Ready Kit



Load Stability Indicator



Cabin Work Lights



Mirrors



PUTTING YOUR WORK ABOVE EVERYTHING

When it comes to JLG® Ground Support, it's all about you. Your productivity. Your profitability. Your uptime. From the purchase of your first piece of equipment straight through to the training, parts and maintenance that follows.



FINANCIAL SOLUTIONS

Maximising your profits. Preserving your cash flow.

Let our financing specialists help choose the program designed specifically for your needs.

AFTERMARKET PARTS

Keep your equipment running at peak performance with genuine replacement parts, accessories, attachments and competitive parts all from one source - JLG.

TRAINING

Knowing your equipment inside and out results in higher productivity on the job. Our instructor-led courses give you the hands-on time you need for success.

SERVICE CENTERS

Your needs. Your uptime. JLG is on the job to fulfill your every need, from repair, same-day parts and much more. We're here to support you.

14 m 6.38 m 2.35 m 2.61 m 3.15 m	17.1 m 6.41 m 2.35 m 2.68 m	
2.35 m 2.61 m 3.15 m	2.35 m	
2.61 m 3.15 m		
3.15 m	2.68 m	_
		_
	3.23 m	_
428 mm	458 mm	
3,600 kg	4,000 kg	
3,000 kg	2,500 kg	
9.5 m	13.9 m	
900 kg	500 kg	
9,880 kg	11,620 kg	
3.81 m	3.85 m	
4 x 4	4 x 4	_
Deutz TCD 3.6 L4	Deutz TCD 3.6 L4	_
STAGE 4	STAGE 4	***
55.4 kW	55.4 kW	_
390 Nm	390 Nm	_
3 Speed forward and reverse. (1st:	5 km/h, 2nd: 10 km/h, 3rd: 20 km/h)	_
Two wheel / four wheel / crab ste	eer with push button select facility	
Mitas 15.5 / 80-24ply	Mitas 14.00-24TGO2	
20 km/h	20 km/h	
10 degrees	10 degrees	n
	3,000 kg 9.5 m 900 kg 9,880 kg 3.81 m 4 x 4 Deutz TCD 3.6 L4 STAFF 55.4 kW 390 Nm 3 Speed forward and reverse. (1st: Two wheel / four wheel / crab ste Mitas 15.5 / 80-24ply 20 km/h	3,000 kg 9.5 m 13.9 m 900 kg 500 kg 9,880 kg 11,620 kg 3.81 m 3.85 m 4 x 4 Deutz TCD 3.6 L4 STAGE 55.4 kW 55.4 kW 390 Nm 3 Speed forward and reverse. (1st: 5 km/h, 2nd: 10 km/h, 3rd: 20 km/h) Two wheel / four wheel / crab steer with push button select facility Mitas 15.5 / 80-24ply Mitas 14.00-24TGO2 20 km/h 20 km/h

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.

14

Deutschland

Tel: +49 (0) 421 693 500 JLG Deutschland GmbH Max-Planck-Straße 21 27721 Ritterhude-Ihlpohl (Bei Bremen)

España

Tel: +34 93 772 47 00 JLG Ibérica, SL Trapadella, 2 Pol. Ind. Castellbisbal Sur 08755 Castellibisbal (Barcelona)

France

Tel: +33 (0) 553 88 31 70 JLG France SAS ZI Guillaume mon Amy CS 30204 Fauillet F-47400 Tonneins

Italia

Tel: +39 02 9359 5210 JLG Industries (Italia) s.r.l. Via Po.22 20010 Pregnana Milanese -MI-

Russia

Tel: +7 (495) 967 79 14 JLG Industries Inc. Vashutinskoe shosse 24b Khimki, Moscow Region 141400 Russian Federation

Sverige

Tel: +46 (0) 8 506 59500 JLG Sverige AB Enköpingsvägen 150 Box 704, 176 77 Järfälla

United Kingdom

Tel: +44 (0) 161 654 1000

JLG Industries (United Kingdom) Limited
Bentley House, Bentley Avenue
Middleton, Greater Manchester
M24 2GP

JLG EMEA BV

Tel: +31 (0) 23 565 5665 Polaris Avenue 63 2132 JH Hoofddorp The Netherlands

JLG Ground Support byba

Tel: +32 (0) 89 77 49 74 Incubathor Thor park 8300 3600 Genk Belgium

Romania Manufacturing Central Europe SRL

Tel: +40 (0) 269 803 974 A. Vlaicu nr. 41 551041 Medias Romania

JLG Industries, Inc. is a leading designer and manufacturer of access equipment and complementary services and attachments.

JLG has manufacturing facilities in the United States, France, Romania and China. Customers throughout Europe, Africa and the Middle East benefit from a network of dedicated sales and service operations designed to deliver the highest levels of support.