

	<b>600S</b>	<b>660SJ</b>
Working Height	20.19 m	22.02 m
Platform Height	18.19 m	20.02 m
Horizontal Outreach	15.29 m	17.40 m
Working Outreach *	15.94 m*	18.05 m*
Swing (Continuous)	360°	360°
Platform Capacity - Unrestricted	270 kg	270 kg
Platform Capacity - Restricted	455 kg	340 kg
Platform Rotator (Hydraulic)	160°	180°
Jib - Overall Length	—	1.83 m
Jib - Range of articulation	—	130° (+70°/-60°)
A. Platform Size	0.91 m x 1.83 m	0.91 m x 1.83 m
B. Overall Width	2.49 m	2.49 m
C. Tailswing (working condition)	1.22 m	1.22 m
D. Stowed Height	2.50 m	2.50 m
E. Overall Length	8.71 m	10.79 m
G. Wheelbase	2.51 m	2.51 m
H. Ground Clearance	0.29 m	0.29 m
Machine weight <sup>1</sup>	9,819 kg	11,603 kg
Maximum Ground Bearing Pressure	5.84 kg/cm <sup>2</sup>	6.07 kg/cm <sup>2</sup>
Maximum Tyre Load	5,788 kg	6,677 kg
Drive Speed 4 x 4 x 2	6.8 km/h	6.8 km/h
Gradeability 4 x 4 x 2	45%	45%
Tyres	355/55D625 Foam Filled	355/55D625 Foam Filled
Axle Oscillation (optional)	0.20 m	0.20 m
Turning Radius - Inside 2WS	2.92 m	2.92 m
Turning Radius - Inside 4WS	1.61 m	1.61 m
Turning Radius - Outside 2WS	5.96 m	5.96 m
Turning Radius - Outside 4WS	3.87 m	3.87 m
Diesel Engine Deutz D2011L04	36.4 kW	36.4 kW
Fuel Tank Capacity	117 L	117 L
Hydraulic System	129 L	129 L
Auxiliary Power	12V DC	12V DC



\* Working outreach is horizontal outreach plus 65cm.  
<sup>1</sup> Certain options or country standards may increase weight and/or dimensions.

